



## INSTALLATION INSTRUCTIONS

### PRODUCT: Weatherall Plus Motorcycle Cover



#### WARNING

In severely windy conditions, “ballooning” of the cover may occur, which may result in the wind causing the motorcycle to tip over. It is strongly recommended that your motorcycle be sheltered whenever high winds are expected. If sheltering is not an option, facing into gusts may reduce the potential for wind damage.



#### WARNING

This cover must be completely removed prior to starting or operating the vehicle. Failure to do so could result in serious injury and/or property damage.



#### NOTE

This cover is not designed for covering your motorcycle while it is trailered or in the back of a pick-up truck.

### 1. INSTALLATION

- ▶ Unfold cover and remove Warranty Card
- ▶ Position the front of the cover on motorcycle. Starting in the front head light area, pull down over the windshield and tuck the elastic hem under the head light. Working toward the rear of the motorcycle, slide the cover down the sides, avoiding snag points. Position the cover around the rear of the motorcycle.
- ▶ Secure belly strap underneath the bike.



#### CAUTION

Mirrors, muffler ends, shifters, brakes and foot pegs are common wear points. Do not allow fabric to “snag” around them. Antennas are capable of puncturing the cover – use extreme care.

### 2. CARE AND CLEANING

- ▶ Your cover requires very little maintenance. Normal dirt and grime should be brushed off with a soft terry cloth or removed with warm water and a mild detergent using a sponge or terry cloth. The cover should be thoroughly dried before using.



#### CAUTION

Do not place in washing machine and do not wring or twist the cover to remove moisture. A water-repellent spray material, such as 3M Scotchguard®, is recommended for increased water resistance. Although protected with UV inhibitors, the fabric may fade in direct sunlight after continuous use. This is normal wear.